

LINE

38201

Ultimate instep protection. Dual density comfort.



TECHNOLOGIES

■ SHOCK ABSORBER

Programmed deformation ovoidal vault system. It redirects the load on the cue by distributing it evenly.

■ MICROTEC PRO

Effective antimicrobial protection. Prevents the development of microorganisms and bad odors.

DRYMAX

Double layer lining. Textile fabric in contact with the foot and non-woven layer as support. Comfort and durability.

RUBBERSKIN

Superficial elastomer seal. It increases chemical and physical resistance.



38201

DESCRIPTION

Model: Welding Ankle Boot

UPPER COMPOUND

Color

Black

Upper

• HQ Full-Grain Leather

Inside

· DRYMAX Lining (bottom part)

Collar

Non-Padded

Tongue

None

■ TOE CAP

Steel

ACCESORIES

Laces

Array

Lace-keepers

Insoles

· Low density rubber comfort insole

PLANT

Other properties

- Electrical Hazard
- Resistant to Hydrocarbons
- Slip Resistant
- Self-Cleaning
- Resistant to Flexing
- Resistant to Abrasion
- Grooves for Stair-Climbing
- Wide Tread Base

Compound

• Dual Density Rubber

Upper plant adhesion

 Cemented with bi-component adhesive and sewn with high-endurance threads

OPTIONALS


- Steel Shank
- Polypropylene Toe-Cap
- PR Puncture Resistant

SIZES

From 6 to 16

SAFETY HAZARDS SPECIFICATIONS













Last review date: 2022/07/22

WWW.FUNCIONALWEB.COM

The content of this document can be changed without previous notice.

© Maincal 2024